

BRONZE SOLAR

BIPV (Building Integrated Photovoltaic)

Address: Abundance Solar Panels Industries – LLC Plot No 7-8, KHIA5, KEZAD, Abu Dhabi, UAE

ABS-Custom Printed Front-Glass BIPV Panels

ENGINEERING DRAWINGS & TECHNICAL PARAMETERS

BRONZE SOLAR

Technical Parameters	
Maximum Rating Power (Pmax)	640 wp
Open Circuit Voltage(Voc)	49.37 V
Maximum Power Voltage (Vmp)	41.93 V
Short Circuit Current (Isc)	15.86 A
Maximum Power Current (Imp)	15.30 A
Module Efficiency (EFF)(%)	23.88 %
Customized Size and Print options available –Power out put up to 50% of actual.	

Mechanical Data	
Solar Cell	Topcon 182.2 x 105 mm G12R ,16BB
Dimensions	2376 mm x 1128 mm x 7.5 mm
Weight	43 kg / 94.79 lbs.(±3%)
Front Glass	3.2 mm, Low Iron,Tempered Glass with Custom Printed
Cell Encapsulation	EPE(Expanded polyethylene) & EVA (Ethylene-Vinyl-Acetate) or Black EVA
Back Glass	4.0 mm Semi Tempered Black Glass
Frame	NA
Junction Box	IP68, 1500VDC, 3 Bypass Diodes- 400mm (Cable length can be customized)







OPERATING CONDITION

Mechanical Load	5400 Pa
Maximum System Voltage	1500VDC
Series Fuse Rating	25 A
Operating Temperature	-40 to 85 °C
Safety application class	Class II
Fire Rating	Class A

TEMPERATURE CHARACTERISTICS

Nominal Module Operating Temperature	43°C ± 2°C
Temperature Coefficient of Isc	+0.05 % / °C
Temperature Coefficient of Voc	-0.25 % / °C
Temperature Coefficient of Pmax	-0.30 % / °C

Address: Abundance Solar Panels Industries – LLC Plot No 7-8, KHIA5, KEZAD, Abu Dhabi, UAE